



## SHRINK TUNNEL COMPACT 1000 Q



Intelligent technology  
for energy-efficient shrinking

Complete product range  
for efficient packaging processes

**Kalfass** 

Results count.

# Shrink Tunnel for large formats

## COMPACT 1000 Q

### The Compact 1000 Q for packaging large products.

The unique ring nozzle heating system with a quadruple-construction design makes it possible to package large products with minimum energy use. The highly effective heat insulation and extremely accurate temperature control ensure perfect packaging results. The tunnel was designed for the upper performance range.



The figure may show optional equipment, ordered separately

### Technical specifications

	Compact 1000 Q
Adjustable working height	800 - 900 mm
Tunnel clearance width, height	1000 mm, 200 / 400 mm
Length of the heated tunnel hood	2800 mm
Power supply	208 - 480 Volt
Continuously adjustable temperature	up to 190°C
Transport speed	10 - 35 Meter/Minute
Installed heating capacity	36 (4 x 9 kW)



The ring nozzle heating system with exactly adjustable air flow control provide uniform heat transfer into the shrink film.

### Your benefits highlighted

- Perfect packaging results using constantly uniform heat energy transfer into the shrink film, regardless of the position on the conveyor belt
- Ring nozzle heating technology with integrated air circulating system for efficient energy recovery
- High level of insulation and compact design ensure fast warm-up times
- Easy adjustment of basic parameters (temperature, air volume and package speed) using continuously adjustable controller
- Intelligent technology ensures constant temperature during operation. Energy-intensive temperature fluctuations are prevented
- Carefully selected components, easy to maintain, maintenance-free plastic mesh-belt

**Solution with Kalfass quality. Competence in the production of a wide range of products, from individual units to packaging systems to integration into production lines.**