

L-sealer with shrink tunnel KC 5040/450 UNIVERSAL



Created for demanding industrial applications



Complete product range for efficient packaging processes

KC 5040/450 Universal

The compact L-sealer KC 5040/450 in combination with high performance shrink tunnel. The qualities of this series of machines become evident when subjected to hard, continuous use. Products such as for example printed material, sets of glassware or oil canisters can all be packed quickly and economically whilst maintaining a high quality.

denter de la constitue de la c



lechnical specifications	KC 5040/450 Universal
Transverse seal bar, length	400 mm
Product clearance height	200 mm
Power supply	208 - 480 Volt
Film, centre-folded film	12 - 80 µm
Transport speed	2,5 - 12 meter / minute
Packaging capacity, max.	20 cycles / minute



Sovereign and reliable. First L-sealer with PLC SIMATIC S7-1200.

Your benfits highlighted

- Economical packaging of a wide range of products
- Effective and absolutely inodorous mode of operation with proven impulse sealing technology using teflonised sealing and cutting wire
- Electromagnetically operated hooks to apply constant pressure during the sealing cycle
- Accurate maintenance of the set sealing time by PLC SIMATIC S7-1200
- Trouble-free sealing and cutting, even with thicker films through defined contact pressure
- Also with plastic mesh belt available
- T-wire-sealing for thick PE-Film 60µm and upwards

Solution based on Kallfass quality. Competence in production of a wide range of packaging machines, from customer taylored systems to packaging systems for integration into production lines.



KALLFASS ist certified according to ISO 9001:2008 **www.kallfass.com** Kallfass Verpackungsmaschinen GmbH Siemensstraße 8 · 72622 Nürtingen · Germany Fon +49 7022 607-0 · Fax -200 · info@kallfass.com

