



Created for demanding industrial applications





KC 5040/450 Universal

The compact L-sealer KC 5040/450 in combination with high performance shrink tunnel. The qualities of this series of machines become evident when subjected to hard, continuous use. Products such as for example printed material, sets of glassware or oil containers can all be packed quickly and economically whilst maintaining a high quality.



The figure may show optional equipment, ordered separately

Technical specifications

	NC 3040/430 Olliveisai
Transverse seal bar, length	400 mm
Product clearance height	260 mm
Power supply	208 - 480 Volt
Film, centre-folded film	12 - 80 μm
Transport speed	2,5 - 12 meter / minute
Packaging capacity, max.	20 cycles / minute







KC 5040/450 Universal

Sovereign and reliable. First L-sealer with PLC SIMATIC S7-1200.

Your benfits highlighted

- Economical packaging of a wide range of products
- Effective and absolutely inodorous mode of operation with proven impulse sealing technology using teflonised sealing and cutting wire
- Electromagnetically operated hooks to apply constant pressure during the sealing cycle
- Precise cycle time achieved by PLC SIMATIC S7-1200
- Trouble-free sealing and cutting, even with thicker films through defined contact pressure
- Also with plastic mesh belt available
- T-wire-sealing for thick PE-Film 60µm and upwards

Solution based on Kallfass quality. Competence in production of a wide range of packaging machines, from customer taylored systems to packaging systems for integration into production lines.