

Fully automatic, intermittent 2-side sealer **SERVO PACKER 1000 T**





Results count.

SERVO PACKER 1000 T

The Servo Packer 1000 T is the intermittent version of the Servo Packer and offers sophisticated, proven technology. User-friendliness is guaranteed by the 7" HM-Interface - Easy Touch KP3 - with its easy and intuitive operation. The clever alternative for creating a film bag in an attractive package design.



| Technical specifications | Servo Packer 1000 T |
|---------------------------|------------------------|
| Cross seal bar, length | 1150 mm |
| Seal bar clearance height | 150 mm |
| Power supply | 400 volt |
| Film, flat film | approx. 11 - 100 µm |
| Transport speed | 10 - 35 meter / minute |
| Packaging capacity, max. | 60 cycles / minute |
| | |



The Servo Packer 1000 T with the intermittent operating principle in customary Kallfass quality

Your benefits highlighted

- Path control: One input of the packing goods parameter in linear dimension for all conveyor belt speeds
- Tight packaging without shrinking
- Attractive package design due to real rectangular film bag
- Very high productivity, flexibility, reliability and availability of the packaging machine
- Fully automatic, intermittent operation
- Maximum flexibility in the packaging process. Use of PE, PO and PLA films

Solutions based on Kallfass quality. Competence in production of a wide range of packaging machines, from customer taylored systems to packaging systems for integration into production lines.



KALLFASS is certificated according to ISO 9001:2008 www.kallfass.com Kallfass Verpackungsmaschinen GmbH Siemensstraße 8 · 72622 Nürtingen · Germany Phone +49 7022 607-0 · Fax -200 · info@kallfass.com

