

Fully automatic 2-side sealer **SERVO PACKER 500**



A true hybrid for
extremely tight packing

Complete product range
for efficient packaging processes

Kalfass 
Results count.

Fully automatic 2-side sealer

Servo Packer 500


The SERVO PACKER 500 is „Kallfass’s fast hybrid“, with motion controlled travelling cross seal bar system, which allows extremely tight packaging, without shrinking. Due to the film transport on both sides, real square plastic bags are generated. These are requirements for accurately fitting seams for cubic products. User-friendliness is guaranteed by the 7” HM-Interface - Easy Touch - with its easy and intuitive operation.



The figure may show optional equipment, ordered separately

Technical specifications

	Servo Packer 500
Cross seal bar, length	550 mm
Product clearance height	200 mm
Power supply	208 - 480 volt
Film, flat film	approx. 11 - 100 µm
Transport speed	5 - 35 m / minute
Packaging capacity, max.	120 cycles / minute



Servo Packer 500. The fast hybrid combines the benefits of a universal side sealer and a film packaging system, making extremely tight packaging possible.

Your benefits highlighted

- Tight packaging without shrinking
- Attractive package design due to real rectangular film bag
- Very high productivity, flexibility, reliability and availability of the packaging machine
- Fully automatic, continuous operation
- Motion controlled travelling cross seal bar system
- Maximum flexibility in the packaging process. Use of PE, PO and PLA films

Solution with Kallfass quality. Competence in the production of a wide range of products, from individual units to packaging systems to integration into production lines.