



Fully automatic, continuous 2-side sealer **SERVO PACKER 500 C**



HIGH SPEED NON-STOP

Complete product range
for efficient packaging processes

Kalfass 

Results count.

Fully automatic, continuous 2-side sealer


SERVO PACKER 500 C

Using its continuous operating principle, the Servo Packer 500 C packs products without STOP and GO at HIGH SPEED and in an extremely tight bag. The result is a real rectangular film bag. The best conditions for accurately fitting seams for cube-shaped products. User-friendliness is guaranteed by the 7 inch HM-Interface - Easy Touch - with its easy and intuitive operation.



Technical specifications

	Servo Packer 500 C
Cross seal bar, length	550 mm
Seal bar clearance height	200 mm
Power supply	400 volt
Film, flat film	approx. 11 - 100 µm
Transport speed	5 - 35 meter / minute
Packaging capacity, max.	150 cycles / minute



The Servo Packer 500 C: At high speed into the film bag.

Your benefits highlighted

- Tight packaging without shrinking
- Attractive package design due to real rectangular film bag
- Very high productivity, flexibility, reliability and availability of the packaging machine
- Fully automatic, continuous operation. Packaging without STOP and GO.
- Motion controlled travelling cross seal bar system
- Maximum flexibility in the packaging process. Use of PE, PO and PLA films

Solutions based on Kalfass quality. Competence in production of a wide range of packaging machines, from customer tailored systems to packaging systems for integration into production lines.