


Continuous motion sleevewrapper SUPER WRAP SERVO



Continuous packaging without STOP and GO





## **Continuous motion sleevewrapper**

## SUPER WRAP 500 SERVO and Super Wrap 800 Servo

The fully automatic, continuous motion sleevewrapper Super Wrap Servo is especially designed for the economical transport- and protective packaging. Accumulative packs from the food sector, newspaper- and magazine-stacks or any other products reliably packed without STOP and GO of the products, thus in continuous motion with up to 50 cycles/minute. Sleevewrapping with high speed.



	Technical specifications	Super Wrap 500 Servo	Super Wrap 800 Servo
	Transverse seal bar, length	550 mm	850 mm
	Seal bar clearance height	up to 400 mm	up to 400 mm
	Product length, min.	150 mm	150 mm
	Power supply	208 - 480 Volt	208 - 480 volt
	Film, flat film	up to 120 μm	up to 80 μm
	Transport speed	5 - 35 meter / minute	5 - 35 meter / minute
	Packaging capacity, max.	50 cycles / minute	50 cycles / minute





The special feature of the Super Wrap Servo: Reliably packaging in continuous motion.

## Your benefits highlighted

- High efficiency, flexibility, reliability and availability of the packaging machine
- Fully automatic, continuous motion operation
- Continuous motion sealing system packed without STOP and GO in continuous motion with up to 50 cycles/ minute
- Seal bar equipped with electromechanic safety device to protect sensitive products
- Continuously heated sealing die with replacable sealing bar
- Free rotating wear free counter seal bar (optional)

Solutions based on Kallfass quality. Competence in production of a wide range of packaging machines, from customer taylored systems to packaging systems for integration into production lines.



